



HD Outdoor P5 Rental Stage LED Screen 1R1G1B For Commercial Advertising

Our Product Introduction

Basic Information

- Place of Origin: China (Mainland)
- Brand Name: TOPLED
- Certification: CE FCC ROHS
- Model Number: P5
- Minimum Order Quantity: Negotiation
- Price: Negotiation
- Packaging Details: Flight case or Standard wooden box
- Delivery Time: 10-15 working days after got deposit
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram
- Supply Ability: 5000 Square Meter/Square Meters per Month



Product Specification

- Usage: Indoor
- Color: Full Color
- Cabinet Size: 640*640mm
- Material: Die Casting Aluminum
- Module Size: 320*160mm
- Warranty: 2 Years
- Highlight: stage led display, led stage curtain screen



Product Description

Commercial Advertising HD TV Outdoor P5 Rental Stage LED Screen For Night Party

Characteristics

1. Bright color, high contrast, good consistency and high brightness to keep the high resolution of the video under the sunlight.
2. Use standard size module, can be arbitrary adjustment measures. Using connection frame steel structure, installation and maintenance is very convenient.
3. By using slim and energy-saving power, muted and temperature control ventilator to enhance the stability and prolong the life span of the screen.
4. By using constant current driving method to keep effect of display in long-term use and prolong the life span effectively.

Normally we accept T/T and Western Union.

Normally we accept T/T and Western Union.

Application

The product is applied to display text, image and video for near viewing distance outdoor. It is mainly used in the entrance of shopping mall, vehicle display, bus station advertising board, hotel, supermarket, gymnasium, stadium, TV station etc.

Specification:

Pixel Pitch	5mm
Pixel Density	40000dots/sq.m
Color Configuration	1R1G1B
LED Package	SMD2727
Display	Full Color
Module Size	320mm x 160mm
Module Resolution	64dots x 32dots
Drive Duty	1/8 Scan
Standard Cabinet Size	640*640mm
Cabinet Weight	11kg
Led Chip	Nationstar / Kinglight
Power	DC 5V, AC110V-220V
Brightness	≥6000 cd/sqm
Viewing Distance	5M
Viewing Angle	H: 140°; V:140°
Refresh Rate	>1920HZ, adjustable by software
Power Input	AC110V/ 220V ±10%, 50HZ
Max Power Consumption	800W/cabinet
Ave. Power Consumption	300W/cabinet
Temperature	-40 ~+65
MTBF	>10,000 Hours
Life Span	>100,000 Hours
Waterproof Level	IP65
Operating Humidity	10%~90% RH
Control Method	Synchronous
Control PC	With DVI Graphic card
Operating System	Win 98, Win2000, XP, Win7, Win8
Certificate	CE, RoHS,ISO9001

Project images:





Beijing Silk Road Enterprise Management Services Co.,LTD



8618888888888



andy@gmail.com



highbrightnessleddisplay.com

Room 402.Dongbao Building,No.19 Dongbao Road,Songjiang,Shanghai 201613,China